

# BETON



## ACRYLIC SEALER FOR CONCRETE AND POROUS FLOORS

- Suitable for porous floors (ex.terracotta floors etc..)
- Anti-dust effect and anti-stain effect
- Resistant to heavy traffic

Acrylic sealer specially designed for very porous floors. Anti-dust effect and resistant to heavy traffic. Excellent anti-stain effect.

### HOW TO USE

After carefully removing wax and any saltpetre deposits, apply two coats of sealer using the special wax applicator (the first coat should be diluted with 50% water to make impregnating easier). Leave to dry approximately 45 min. between one coat and the next.



### DILUTION

Ready to use.

### TECHNICAL DATA

**ASPECT:** Opaque liquid

**COLOR:** Creamy white

**PERFUME:** Technical

**COV:** 0,00%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
7,7 ± 0,5		1.018			21 ± 1

### WARNINGS

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Contents METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE: May produce an allergic reaction.

## BETON

### NOTES

Check that the sealer adheres to concrete floors and do not apply BETON at temperatures below 10° C. Keep away from freezing. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product. Sutter Professional cannot be considered liable for any damages due to improper product use.

**Only for professional use. Safety data sheet available on request.**

### PACKAGING

Code	Size	Quantity	Pallet
3822	Kg 5	4	9x4=36