

PB 28



ANTI-SLIP METAL CROSS-LINKED POLYMER EMULSION

- Anti-slip effect tested by UL laboratories
- Wash resistant with alcohol-based disinfectants
- Self-polishing effect, can also be used on stone floors



Emulsion formulated with acrylic and polyurethane polymers to guarantee the formation of a high gloss, resistant and flexible film. Excellent resistance to abrasion. Resistant to washing with disinfectants, even alcohol based, if used correctly and with the correct dilution. Registered with Underwriters Laboratories Inc. as anti-slip, high resistance wax.

HOW TO USE

After carefully removing wax using a wax stripper from the SUTTER PROFESSIONAL range, apply two coats of wax using the special wax applicator. Leave to dry approximately 30 - 60 min. between one coat and the next. Also suitable for UHS spray cleaning or spray buffing maintenance.



DILUTION

Ready to use.

TECHNICAL DATA

ASPECT: Opaque liquid

COLOR: Creamy white

PERFUME: Technical

COV: 0,00%

PH	Active substance [%]	Density (g/ml)	Pressure (bar)	Viscosity (cP)	Total dry residue [%]
9,0 ± 0,5		1.038			21 ± 1

! WARNINGS

May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Avoid breathing vapours. Wear protective gloves and eye/face protection. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Contains METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE. May produce an allergic reaction. Contains ZINC AMMONIA CARBONATE COMPLEX.



WARNING

📄 NOTES

Protective wax for floors. Do not apply PB 28 at temperatures below 10° C. Keep away from freezing. Some floors may be difficult to penetrate and/or anchor the treatment. Check adherence in a small area of the floor before applying the product. Sutter Professional cannot be considered liable for any damages due to improper product use.

Only for professional use. Safety data sheet available on request.

📦 PACKAGING

Code	Size	Quantity	Pallet
4016	Kg 5	4	9x4=36